CRAFTMARK PIPE MARKERS SINCE 1959

U.S.A



PRODUCT SUBMITTAL DATA DURAMARK™ SELF-STICK PIPE MARKER



<u>DESCRIPTION</u>: DURAMARK™ is a durable indoor/outdoor pipe marker system. Sturdy .004" vinyl printed using UV screen inks which hold up to sun & weather. <u>USE</u>: Use to identify piping systems per ASME (ANSI) A13.1 2007 when used with either pipe banding tape or direction flow arrow tape. Can be used indoor or outdoor.

COMPLIANCE: Complies 100% to ASME (ANSI) A13.1 2007 Scheme for the Identification of Piping Systems for color, color field width & letter size.

Complies with ANSI Z535.1 Safety Color Code

•LEED Compliance: This product is in compliance with Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule#1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC).

Craftmark's Duramark™ Pipe Marker is a practical, economical marking system featuring bold gothic characters printed on bright ASME conforming colors to provide unmistakable identification of pipe contents. Duramark™ Pipe Markers are manufactured with the industries most durable, long lasting vinyl with an aggressive acrylic adhesive. Now available in 5 stock sizes to mark pipes with outside diameter of 3/4" to over 10". Craftmark sizes, color schemes and letter height all meet ASME (ANSI) A13.1 -Scheme for the Identification of Piping Systems.

FEATURES

- · Indoor / Outdoor Use
- Meets ASME (ANSI) A13.1 100%
- Bright ASME conforming background colors!
- In-Stock legends for immediate shipment.
- · Letter height meets ASME specifications.
- Color field width meets ASME specifications
- · Matching arrow tape available.
- Durable, premium grade, indoor/outdoor vinyl
- Rugged UV screens inks
- · Excellent adhesion to piping and insulation.
- Use with arrow tape or individual arrows to indicate flow direction.
- · Choose from over 385 stock legends.
- · Custom markers available with no minimums!

DURAMARK Application Guide

For pipes with outside diameters of 3/4" to 11/4".

1/2" Characters

Style 1 XSM

1/2" DEIONIZED WATER 3/4"

For pipes with outside diameters of 11/2" to 2". 3/4" Characters

• Style 1 SM.

3/4" COMPRESSED AIR 11/2

For pipes with outside diameters of 21/4" to 6". 1 1/4" Characters

• Style 1



For pipes with outside diameters of 6" to 10".

• Style 1 LG² 1/2" Characters



For pipes with outside diameters of over 10". 3 1/2" Characters

Style 1 XLG



STANDARD COLORS

FLAMMABLE FLUIDS

POTABLE, COOLING, BOILER FEED & OTHER

COMPRESSED AIR

FIRE QUENCHING FLUIDS

TOXIC & CORROSIVE FLUIDS

COMBUSTIBLE FLUIDS

USER DEFINED

USER DEFINED

USER DEFINED

USER DEFINED

DURAMARK™ SELF-STICK PIPE MARKER (Continued)

	rmanent, Aggressive acrylic pressure sensitive adhesive. Sticks to most pipe and pipe overing materials.
	Tatoling matorials.
SURFACE PREI	PARATION: Surface should be dry, oil free, dirt free and above the minimum application temperature.
SERVICE TEMP	PERATURE: -40°F to 200°F (-40°C to 93°C)
APPLICATION 1	ΓΕΜΡΕRATURE: Minimum application temperature of 50°F (10°C)
AVERAGE OUT	DOOR DURABILITY: 5 years outdoor - mid continental U.S.
CHEMICAL RES	SISTANCE: VERY GOOD
MOISTURE RES	SISTANCE: EXCELLENT moisture resistance
ABRASION RES	SISTANCE: VERY GOOD abrasion resistance
GLOSS: 40 Ga	rdner units (20° test)
STORAGE STAI	BILITY: 2 years typical at 70°F (21°C) at 50% relative humidity
<u> </u>	JOB: