





## PRODUCT SUBMITTAL DATA DURAMAX METAL PHOTO TAGS



<u>DESCRIPTION:</u> Duramax is the most durable, long lasting tag available. Outdoor durability is 25 years. Available Black on Natural background or Natural on Black background.

<u>USE:</u> For a wide array of marking requirements from Valve Tags, Warranty Tags & Equipment ID.

Duramax Photosensitive Anodized Aluminum combines extreme durability in harsh environments with a high-quality, long-lasting appearance. Duramax nameplates and tags function perfectly for years, maintaining their original appearance under an array of challenging conditions including heat, humidity, long term exposure to weather, UV and other outdoor conditions, salt spray, abrasion, industrial solvents, chemicals & more.

- .020 Anodized Aluminum
- · 6 stock sizes available.
- · Custom sizes also available.
- 25 Year outdoor life.
- UV Resistant
- · Abrasion resistant
- · Chemical resistant
- Moisture resistant
- Corrosion resistant
- Meets Mil Stds

Mil-P-I5024F

Mil-P-514D

Mil-P-19834B

Mil-A-8625E

	Anodic Layer The glass-clear, sapphire- hard anodized layer resists chemicals, paint, abrasion and dirt.
'	Sealed Image Black graphics are metallic silver particles that hold up to extreme heat and sunlight exposure.
Th	luminum Layer e rigid aluminum base will not el, crack or delaminate.

DATE: / /	JOB:	 	
CONTRACTOR:			

## **DURAMAX METAL PHOTO TAGS (Continued)**

ADHESIVE: 2 mil permanent acrylic backing available on this product.  SURFACE PREPARATION: N/A with holes. For adhesive applied, surface must be clean, dry & oil/rust free.  SERVICE TEMPERATURE: -40°F to 250°F for adhesive backed40°F to 750°F for screw attached.  APPLICATION TEMPERATURE: 50°F for adhesive backed. N/A for screw attached.  AVERAGE OUTDOOR DURABILITY: 20-25 years  CHEMICAL RESISTANCE: Excellent resistance to salt spray, industrial solvents, chemicals & more.  MOISTURE RESISTANCE: EXCELLENT  ABRASION RESISTANCE: EXCELLENT  GLOSS: 40 Gardner Units.  STORAGE STABILITY: Indefinite with screw holes. 2-3 years with adhesive backing when stored at 70°F at 50% relative humidity.		
For adhesive applied, surface must be clean, dry & oil/rust free.  SERVICE TEMPERATURE: -40°F to 250°F for adhesive backed40°F to 750°F for screw attached.  APPLICATION TEMPERATURE: 50°F for adhesive backed. N/A for screw attached.  AVERAGE OUTDOOR DURABILITY: 20-25 years  CHEMICAL RESISTANCE: Excellent resistance to salt spray, industrial solvents, chemicals & more.  MOISTURE RESISTANCE: EXCELLENT  ABRASION RESISTANCE: EXCELLENT  GLOSS: 40 Gardner Units.	ADHESIVE: 2 mil peri	manent acrylic backing available on this product.
For adhesive applied, surface must be clean, dry & oil/rust free.  SERVICE TEMPERATURE: -40°F to 250°F for adhesive backed40°F to 750°F for screw attached.  APPLICATION TEMPERATURE: 50°F for adhesive backed. N/A for screw attached.  AVERAGE OUTDOOR DURABILITY: 20-25 years  CHEMICAL RESISTANCE: Excellent resistance to salt spray, industrial solvents, chemicals & more.  MOISTURE RESISTANCE: EXCELLENT  ABRASION RESISTANCE: EXCELLENT  GLOSS: 40 Gardner Units.		TIONI NIZA SULLI
APPLICATION TEMPERATURE: 50°F for adhesive backed.  N/A for screw attached.  AVERAGE OUTDOOR DURABILITY: 20-25 years  CHEMICAL RESISTANCE: Excellent resistance to salt spray, industrial solvents, chemicals & more.  MOISTURE RESISTANCE: EXCELLENT  ABRASION RESISTANCE: EXCELLENT  GLOSS: 40 Gardner Units.  STORAGE STABILITY: Indefinite with screw holes.	SURFACE PREPARA	
N/A for screw attached.  AVERAGE OUTDOOR DURABILITY: 20-25 years  CHEMICAL RESISTANCE: Excellent resistance to salt spray, industrial solvents, chemicals & more.  MOISTURE RESISTANCE: EXCELLENT  ABRASION RESISTANCE: EXCELLENT  GLOSS: 40 Gardner Units.  STORAGE STABILITY: Indefinite with screw holes.	SERVICE TEMPERAT	
CHEMICAL RESISTANCE: Excellent resistance to salt spray, industrial solvents, chemicals & more.  MOISTURE RESISTANCE: EXCELLENT  ABRASION RESISTANCE: EXCELLENT  GLOSS: 40 Gardner Units.  STORAGE STABILITY: Indefinite with screw holes.	APPLICATION TEMP	
MOISTURE RESISTANCE: EXCELLENT  ABRASION RESISTANCE: EXCELLENT  GLOSS: 40 Gardner Units.  STORAGE STABILITY: Indefinite with screw holes.	AVERAGE OUTDOOF	R DURABILITY: 20-25 years
ABRASION RESISTANCE: EXCELLENT  GLOSS: 40 Gardner Units.  STORAGE STABILITY: Indefinite with screw holes.	CHEMICAL RESISTA	NCE: Excellent resistance to salt spray, industrial solvents, chemicals & more.
GLOSS: 40 Gardner Units.  STORAGE STABILITY: Indefinite with screw holes.	MOISTURE RESISTA	NCE: EXCELLENT
STORAGE STABILITY: Indefinite with screw holes.	ABRASION RESISTA	NCE: EXCELLENT
	GLOSS: 40 Gardner	Units.
	STORAGE STABILITY	Y: Indefinite with screw holes. 2-3 years with adhesive backing when stored at 70°F at 50% relative humidity.
E: <u>//</u>	E: <u>//</u>	JOB:
NTRACTOR:	NTRACTOR:	