



PRODUCT SUBMITTAL DATA

DIRECTION FLOW - ARROW TAPE



CRAFTMARK'S ARROW TAPE is the finishing touch for our Duramark pipe marker system. Combines color coding with arrows for cost & labor savings!

- Ultra-Durable self stick vinyl
- Matching color combinations meet ASME(ANSI) A13.1 standards
- Serves to secure markers to pipe as well as indicate flow direction
- Provides 360° visibility of flow direction
- 30 yard rolls
- Available in 5 stock widths!
- Available in custom color combinations

Pipe Diameter	Number of Bands Per Roll	Pipe Diameter	Number of Bands Per Roll
1"	344	6"	57
2"	172	7"	49
3"	115	8"	43
4"	86	9"	38
5"	68	10"	34

DESCRIPTION: Indoor/Outdoor grade 4 mil vinyl is excellent for indicating flow direction along with Craftmark Pipe Markers.

USE: Direction Flow Arrow Tape can used by itself to indicate flow direction as well as with Duramark Pipe Markers to comply 100% to ASME (ANSI) A13.1-2007.

COMPLIANCE: ASME (ANSI A13.1-2007 Scheme for the Identification of Piping Systems).

Ansi Z535.1 Safety Color Codes.

•**LEED Compliance:** This product is in compliance with Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule#1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC).

Widths Available: 1/2", 1", 2", 4", 6"

•Tape Width Guideline

TAPE SIZE	USE WITH MARKER SIZE
1/2" x 30 yds	1 XSM
1" x 30 yds	1 SM
2" x 30 yds	1
4" x 30 yds	1LG
6" x 30 yds	1 XLG

•STANDARD COLORS

FLAMMABLE FLUIDS

POTABLE, COOLING, BOILER FEED & OTHER

COMPRESSED AIR

FIRE QUENCHING FLUIDS

TOXIC & CORROSIVE FLUIDS

COMBUSTIBLE FLUIDS

USER DEFINED

USER DEFINED

USER DEFINED

USER DEFINED

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____

DIRECTION FLOW - ARROW TAPE (Continued)

ADHESIVE: Permanent, Aggressive acrylic pressure sensitive adhesive. Sticks to most pipe and pipe covering materials.

SURFACE PREPARATION: Surface should be dry, oil free, dirt free and above the minimum application temperature.

SERVICE TEMPERATURE: -40°F to 200°F (-40°C to 93°C)

APPLICATION TEMPERATURE: Minimum application temperature of 50°F (10°C)

AVERAGE OUTDOOR DURABILITY: 5 years outdoor - mid continental U.S.

CHEMICAL RESISTANCE: VERY GOOD

MOISTURE RESISTANCE: EXCELLENT moisture resistance

ABRASION RESISTANCE: VERY GOOD abrasion resistance

GLOSS: 40 Gardner units (20° test)

STORAGE STABILITY: 2 years typical at 70°F (21°C) at 50% relative humidity

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____
