



## PRODUCT SUBMITTAL DATA ENGRAVED PLASTIC NAMEPLATES



<u>DESCRIPTION:</u> Durable plastic with contrasting surface & core color layers

<u>USE:</u> For Indoor marking of commercial & industrial equipment & facilities.

CRAFTFLEX flexible plastic nameplates and signs are made to your exact specifications. Your information is engraved deeply into 2-ply 1/16" or 1/8" plastic exposing a contrasting inner core color. 18 stock sizes-choose holes or adhesive backing. All sides are chamfered for a clean, finished appearance.

## STANDARD COLORS AVAILABLE

**RED/WHITE** 

GREEN/WHITE
YELLOW/BLACK
DI ACK/MUITE

WHITE/BLACK

BLUE/WHITE

**ORANGE/WHITE** 

VIOLET/WHITE

**GRAY/BLACK** 

**BROWN/WHITE** 

DATE: / /	JOB:		
CONTRACTOR:			

## **ENGRAVED PLASTIC NAMEPLATES (Continued)**

SERVICE TEMPERATURE: -40°F to 175°F  APPLICATION TEMPERATURE: N/A for screw applied/holes.  AVERAGE OUTDOOR DURABILITY: 6 months- not recommended  CHEMICAL RESISTANCE: GOOD  MOISTURE RESISTANCE: EXCELLENT  ABRASION RESISTANCE: EXCELLENT  GLOSS: 60 Gardner units  STORAGE STABILITY: Indefinite for screw/hole attached.  2-3 years for adhesive backed when stored at 70°F at 50% relative humidity.  E:/_/ JOB:	
APPLICATION TEMPERATURE: N/A for screw applied/holes.  AVERAGE OUTDOOR DURABILITY: 6 months- not recommended  CHEMICAL RESISTANCE: GOOD  MOISTURE RESISTANCE: EXCELLENT  ABRASION RESISTANCE: EXCELLENT  GLOSS: 60 Gardner units  STORAGE STABILITY: Indefinite for screw/hole attached. 2-3 years for adhesive backed when stored at 70°F at 50% relative humidity.  E:/_/ JOB:	SURFACE PREPARATION: N/A for screw applied/holes.
AVERAGE OUTDOOR DURABILITY: 6 months- not recommended  CHEMICAL RESISTANCE: GOOD  MOISTURE RESISTANCE: EXCELLENT  ABRASION RESISTANCE: EXCELLENT  GLOSS: 60 Gardner units  STORAGE STABILITY: Indefinite for screw/hole attached. 2-3 years for adhesive backed when stored at 70°F at 50% relative humidity.  E: / / JOB:	SERVICE TEMPERATURE: -40°F to 175°F
CHEMICAL RESISTANCE: GOOD  MOISTURE RESISTANCE: EXCELLENT  ABRASION RESISTANCE: EXCELLENT  GLOSS: 60 Gardner units  STORAGE STABILITY: Indefinite for screw/hole attached. 2-3 years for adhesive backed when stored at 70°F at 50% relative humidity.  E:/_/ JOB:	APPLICATION TEMPERATURE: N/A for screw applied/holes.
MOISTURE RESISTANCE: EXCELLENT  ABRASION RESISTANCE: EXCELLENT  GLOSS: 60 Gardner units  STORAGE STABILITY: Indefinite for screw/hole attached. 2-3 years for adhesive backed when stored at 70°F at 50% relative humidity.  E:// JOB:	AVERAGE OUTDOOR DURABILITY: 6 months- not recommended
ABRASION RESISTANCE: EXCELLENT  GLOSS: 60 Gardner units  STORAGE STABILITY: Indefinite for screw/hole attached. 2-3 years for adhesive backed when stored at 70°F at 50% relative humidity.  E:/_/ JOB:	CHEMICAL RESISTANCE: GOOD
GLOSS: 60 Gardner units  STORAGE STABILITY: Indefinite for screw/hole attached. 2-3 years for adhesive backed when stored at 70°F at 50% relative humidity.  E: / / J JOB:	MOISTURE RESISTANCE: EXCELLENT
STORAGE STABILITY: Indefinite for screw/hole attached. 2-3 years for adhesive backed when stored at 70°F at 50% relative humidity.  E:/_/_ JOB:	ABRASION RESISTANCE: EXCELLENT
2-3 years for adhesive backed when stored at 70°F at 50% relative humidity.  E: / / _ / _ JOB:	GLOSS: 60 Gardner units
	E: <u>///</u> JOB:
	ITRACTOR: