



# PRODUCT SUBMITTAL DATA ROLLMARK V SELF-STICK ROLLFORM PIPE MARKER



Craftmark's Rollmark V is ideal for all pipe marking jobs. Easy to use Rollmark V comes with pre-slit arrows so they can be used to indicate flow in either direction. Rollmark V comes with 50 legends and 50 arrows per roll. Available in 3 sizes to fit most pipe jobs up to 6" diameter.

#### FEATURES

- Ultra-durable self-stick vinyl for indoor/outdoor use.
- Available in 3 sizes.
- Full 50 legends / 50 arrows per roll.
- 85 stock legends.
- · Custom available.
- Meets ASME (ANSI) A13.1 2007

<u>DESCRIPTION</u>: Self-adhesive rolls of pre-printed stock and custom pipe markers. With acrylic pressure sensitive adhesive backing sturdy 4 mil vinyl.

<u>USE:</u> Use to identify piping systems. Designed for all pipe marking jobs.

<u>COMPLIANCE</u>: Complies with ASME (ANSI) A13.1 2007 Scheme for the Identification of Piping Systems for color, color field width & letter size.

• ROLLMARK V Application Guide	• STANDARD COLORS
Small 1" x 8" - <sup>3</sup> /4" Letters	FLAMMABLE FLUIDS
WATER HOT WATER	POTABLE, COOLING, BOILER FEED & OTHER
WATE	COMPRESSED AIR
Large 2" x 12" - 1 <sup>1</sup> /4" Letters	FIRE QUENCHING FLUIDS
	<b>TOXIC &amp; CORROSIVE FLUIDS</b>
	COMBUSTIBLE FLUIDS
	USER DEFINED
X Large 4" x 24" - 3" Letters	USER DEFINED
ESSED AIR COMPRESSED AIR	USER DEFINED
COSED	USER DEFINED

### DATE: / / JOB:\_\_\_

#### CONTRACTOR:

## **ROLLMARK V SELF-STICK ROLLFORM PIPE MARKER (Continued)**

ADHESIVE: Permanent, aggressive acrylic pressure sensitive adhesive. Sticks to most pipe and pipe covering materials.

SURFACE PREPARATION: Surface should be dry, oil free, dirt free and above the minimum application temperature.

SERVICE TEMPERATURE: -40°F to 200°F (-40°C to 93°C)

APPLICATION TEMPERATURE: Minimum application temperature of 50°F (10°C)

AVERAGE OUTDOOR DURABILITY: 5 years outdoor - mid continental U.S.

CHEMICAL RESISTANCE: VERY GOOD

MOISTURE RESISTANCE: EXCELLENT MOISTURE RESISTANCE

ABRASION RESISTANCE: VERY GOOD ABRASION RESISTANCE

GLOSS: 40 Gardner units (20° test)

STORAGE STABILITY: 2 years typical at 70°F (21°C) at 50% relative humidity.

DATE: / / JOB:\_\_\_\_\_

CONTRACTOR:

CRAFTMARK • www.craftmarkid.com • 1.800.627.5255 • Fax 1.800.889.3141 • 3212 S.Cravens • Ft. Worth, Texas • USA